

Clicka Press

Roof

Wall

Floor

Sawing

Timber Jointing

Production Tools



- Adjustable up to 25 tonnes of pressing force
- Interlocked two-hand control operation
- Top platen swivels to the rear to clear the work surface
- Hydraulic system ensures a fast cycle time and an efficient 1 HP motor
- Many years of use in the timber industry
- Ergonomic working height

Clicka Press

The Clicka press has been used within the roof truss industry for some years in Australia and overseas. It is a very simple but robust piece of equipment that achieves its desired purpose for minimal capital cost.

The simple pushbutton operational controls include a two-hand interlocked safety system that will immediately cease downward pressing once either button is released. Both buttons must be pressed within 0.5 seconds of each other.

A swivel head design of the top platen allows operators to have a clear work surface prior to pressing. Its effortless movement ensures minimal operator fatigue.

The unique and efficient hydraulic system allows a pressing force of up to 25 tonnes with a relatively small electric motor. The pressing force and stroke can be easily adjusted on the press head.

The system's compact design allows for very easy installation that can be carried out by most production staff.

SPECIFICATIONS

		Dimensions
Press capacity (tonnage)		25T adjustable
Overall dimensions (std unit)	– width	mm 1000
	– depth (overall)	mm 1020
	– height (overall)	mm 1410
Motor size		HP 1.0
Maximum stroke		mm 90
Platen size (upper)	– width	mm 500
	–depth	mm 450
Weight (approx)		kg 1200
Installation requirements		
Power		415V, 3 phase, 10A
Air		N/A
Foundation		Level, sound concrete floor in both directions

RELATED EQUIPMENT

- Roller conveyors
- Pre-assembly bench