

Component Bench

Roof

Wall

Floor

Sawing

Timber Jointing

Production Tools



- Fast and efficient wall frame component manufacture
- Adjustable 'walk thru' capability
- Standard pitches allow for quick set up with no marking
- Inbuilt materials handling assists lifting the finished product
- Squaring fences add to quality of wall frame

Component Bench

Pryda's Component Bench has been developed as a result of customer feedback on wishing to safely and easily manufacture wall frame components. It can also be used for the manufacture of small and non-standard wall frames.

The system's split table tops allow flexibility for varying height components or wall frames. It also provides a "walk-thru or walk-around" capability, resulting in a safer work environment. The work surfaces are designed to accommodate either full component assemblies or simply the "over and under" arrangements.

Its top work surface incorporates a series of standard pitches for typical wall frames, allowing quick setting out with only minimal or no marking or measuring. The 900mm work height removes the need for undue bending and twisting.

Inbuilt materials handling assists the lifting and movement of finished product to the next stage of the wall frame manufacturing process. The side fences provide a squaring reference to the component without impeding the nailing process.

SPECIFICATIONS

		Dimensions
Overall dimensions (std unit)	– width	mm 3670
	– depth	mm 3750
	– height (overall)	mm 950
Work height (std)	mm	900
Floor rail height	mm	40
Floor rail track centres (std)	mm	3390
Weight (approx)	kg	300
Installation requirements		
Power		N/A
Air		5 cfm, 100 psi
Foundation		Level, sound concrete floor in both directions

RELATED EQUIPMENT

- Component transfer skates
- Materials handling trolley
- PlantNet production management system